PARADOR

Design floor Vinyl Basic 30

Product quality		
Format		1207 x 216 x 9,4 mm
Packaging	**Pack:**	7 elements / 1.825 m² / 17.00 kg
	Palette:	36 packs / 65.700 m² / 627.00 kg
Tolerances (requirement EN 16511:2023)		
Squareness of the elements (≤ 0.20 mm)		≤ 0,20 mm/m
Determination of linearity (≤ 0.30 mm/m)		≤ 0,15 mm/m
Flatness concave / convex	**lenthwise (≤ 0.50/≤ 1.0 %)**	≤ 0,35 / ≤ 1,0 %
	wide (≤ 0.15/≤ 0.20 %)	≤ 0,10 / ≤ 0,10 %
Surface flushness	**(average ≤ 0.10 mm)**	average ≤ 0.10 mm
	(max. ≤ 0.15 mm)	max. ≤ 0.15 mm
Opening between installed elements	**(average ≤ 0.15 mm)**	average ≤ 0.05 mm
	(max. ≤ 0.20 mm)	max. ≤ 0.10 mm

Guarantee (According Parador guarantee conditions)		**Notes**
Domestic area	Commercial area	- not suitable for all-over adhesion - cleaning and maintenance see instructions - technical changes reserved
15 years	5 years	

EN 14041:2004/AC:2006

ÉMISSIONS DANS L'AIR INTÉRIEUR A+ A+ A B C

Classification

Utility class 23 = domestic areas with intensive use	Utility class 31 = commercial areas with low use
The design floor meets all requirements of the designated utility class.	

Requirements / properties		**Test method**	**Rating**
	Wear layer	ISO 24340	0,3 mm
	Surface Coating		PUR
Bfl-s1	Reaction to fire	EN 13501-1	B_{fl} s1
DS	Slip resistance	EN 13893 EN 14041	μ ≥ 0,35 DS
	Staining resistance	EN 438-2	Category 1 + 2: level 4, slight change Category 3: level 3, moderate change
	Light fastness	EN ISO 105 – B02	Blue wool scale: Stage ≥ 6
	Resistance to roller castor chairs	EN ISO 4918	Type W, no visible changes
	Thermal resistance Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier.	EN ISO 10456	0,068 m²*K/W
	Moving a furniture leg	ISO 16581	No visible damage (foot type 0)
	Indentation-residual	EN ISO 24343-1	≤ 0,10 mm
E1 HCHO	Formaldehyde emission (E1 = 0.1 ppm)	EN 16516	≤ 0,05 ppm
	Acoustical - Impact noise reduction	ISO 717-2	15 dB (on Akustik-Protect 100) 16 dB (on PE film)
	Abrasion	EN 15468 Annex A	≥ 1.500 rev.
	Impact resistance	EN 13329 Annex F	≥ 800 mm
	Thickness swelling	ISO 24336 (≤ 18%)	≤ 16%
	Water resistance	ISO 4760	Requirements met (24h)
	Slip resistance on an inclined plane	EN 16165, Annex B	Brushed, wood texture: R9 / Vivid texture: R10
	Disposal	EAK-Code-number	17 02 03