Cliqs_FSC_Linoleum_1189x210x150 25.12.12 09:18 Seite 1

Parquet

FSC 100% Mixed Sources FSC® C011497

REAL WOOD www.realwood.eu

WICANDERS

AMORIM Excellence in flooring

Parquet

Variable 0210/2 Nr. 1189x210x150 Tak Cup Parquet

Cliqs/Click Parquet Laminate Flooring

1.154.487.100

Regulation No 1907/2006 (REACH) Annex XVII Entry 50 — Contains Isocyanates

Regulation No 1907/2006 (REACH) Annex XVII Entry 53 — Contains Methylene diphenyl diisocyanate

Volume of formaldehyde: E1

Emission of pentachlorophenol: ≤ 5 ppb

CE

Fyr ikke ned i åbne ild eller andre tændkilder. Undgå at udsætte produkt for gnister og varme.

Brugsklasse: 23 — EN 13329:2006+A1:2008

Formaldehydemission: E1 — EN 13986:2004+A1:2015

Pentachlorophenol: ≤ 5 ppb — EN 13986:2004+A1:2015

Brandklasse: Cfl-s1 — EN 13986:2004+A1:2015

Varmeledningsevne: 0,15 W/(m·K) — EN 13986:2004+A1:2015

Vandtæthed: Vandtæt i 24 timer — EN 13329:2006+A1:2008

Slidstyrkegruppe: AC4 — EN 13329:2006+A1:2008

Slagfasthed: 6 mm — EN 13329:2006+A1:2008

Dampgennemtrængelighed: μ > 2000 — EN 13329:2006+A1:2008

Varmeledningsevne: 0,15 W/(m·K) — EN 13329:2006+A1:2008

Frigivelse af farlige stoffer: Overholder gældende krav — EN 13329:2006+A1:2008

Frigivelse af pentachlorophenol: ≤ 5 ppb — EN 13329:2006+A1:2008

Frigivelse af formaldehyd: E1