PARADOR

Design floor Vinyl Basic 2.0

Product quality

Format		1219 x 229 x 2 mm
Packaging	**Pack:**	16 elements / 4,466 m² / 17,680 kg
	Pallet:	54 packs / 241.164 m² / 984.720 kg

Tolerances EN ISO 10582

Weight per unit area	≥ 3.700 g/m²
Squareness of the elements (≤ 0.25 mm)	≤ 0,10 mm/m
Determination of linearity (≤ 0.35 mm/m)	≤ 0,20 mm/m
Dimensional stability after exposure to heat (≤ 0,15 %)	≤ 0,15 %
Curling after exposure to heat (≤ 1mm)	≤ 1mm

Guarantee (According Parador guarantee conditions)		**Notes**
Domestic area	Commercial area	- only suitable for all-over adhesion - cleaning and maintenance see instructions - technical changes reserved
15 years	5 years	

CE
EN 14041:2004/AC:2006

ÉMISSIONS DANS L'AIR INTÉRIEUR A+ A+ A B C

CERTIFIED SUSTAINABLE PRODUCT QNG READY SENTINEL HOLDING INSTITUT

THIRD-PARTY VERIFIED EPD ISO 14025 and EN 15804 Institut Bauen und Umwelt e.V.

Classification

Utility class 23 = domestic areas with intensive use	Utility class 31 = commercial areas with low use

The design floor meets all requirements of the designated utility class.

Requirements / properties		**Test method**	**Rating**
	Wear layer	EN ISO 24340	0,3 mm
	Surface Coating		PUR
Bfl-s1	Reaction to fire	EN 13501-1	B_{fl} s1
DS	Slip resistance	EN 13893 EN 14041	μ ≥ 0,30 DS
	Staining resistance	ISO 26987	Index 0, Not affected
	Light fastness	EN ISO 105 – B02	Blue wool scale: Stage ≥ 6
	Resistance to roller castor chairs	ISO 4918	Type W, no visible changes
	Thermal resistance Suitable for installation over underfloor heating	EN 12664	0,012 m²*K/W
	Moving a furniture leg	EN 424	No visible changes
	Indentation-residual	EN ISO 24343-1	≤ 0,10 mm
	Water resistance	EN 317	waterproof
	Slip resistance on an inclined plane	EN 16165, Annex B	Brushed texture: R9 / Vivid texture: R10
	Disposal	EAK-Code-number	20 01 39