

Product quality		
Format	1219 x 229 x 2 mm	
Packaging	Pack:	16 elements / 4,466 m ² / 17,680 kg
	Pallet:	54 packs / 241.164 m ² / 984.720 kg
Tolerances EN ISO 10582		
Weight per unit area	≥ 3.700 g/m ²	
Squareness of the elements (≤ 0.25 mm)	≤ 0,10 mm/m	
Determination of linearity (≤ 0.35 mm/m)	≤ 0,20 mm/m	
Dimensional stability after exposure to heat (≤ 0,15 %)	≤ 0,15 %	
Curling after exposure to heat (≤ 1mm)	≤ 1mm	
Guarantee (According Parador guarantee conditions)		Notes
Domestic area	Commercial area	- only suitable for all-over adhesion
15 years	5 years	- cleaning and maintenance see instructions
- technical changes reserved		
    		

Classification		
		
Utility class 23 = domestic areas with intensive use		Utility class 31 = commercial areas with low use
The design floor meets all requirements of the designated utility class.		
Requirements / properties	Test method	Rating
 Wear layer	EN ISO 24340	0,3 mm
 Surface Coating		PUR
 Reaction to fire	EN 13501-1	B _n s1
 Slip resistance	EN 13893 EN 14041	μ ≥ 0,30 DS
 Staining resistance	ISO 26987	Index 0, Not affected
 Light fastness	EN ISO 105 - B02	Blue wool scale: Stage ≥ 6
 Resistance to roller castor chairs	ISO 4918	Type W, no visible changes
 Thermal resistance Suitable for installation over underfloor heating	EN 12664	0,012 m ² *K/W
 Moving a furniture leg	EN 424	No visible changes
 Indentation-residual	EN ISO 24343-1	≤ 0,10 mm
 Water resistance	EN 317	waterproof
 Antimicrobial activity	ISO 22196	Antibacterial
 Slip resistance on an inclined plane	EN 16165, Annex B	Brushed texture: R9 / Vivid texture: R10
 Disposal	EAK-Code-number	20 01 39

Changed:	QMB Parador	File:	PA_TDS_Designboden_Vinyl_Basic-2.0_EN_20231001
Date:	01.01.2018	Latest update at:	www.parador.de/en/services/downloads/design-flooring
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.10.2023