

MADRID

RADICI
CARPET



CONSTRUZIONE	CONSTRUCTION	TECHNIQUE DE FABRICATION	HERSTELLUNGSVERFAHREN
TUFTING RICCIO- SCROLL 1/10"	TUFTED LOOP PILE -SCROLL 1/10"	TUFTED BOUCLÉ -SCROLL 1/10"	GETUFTED SCHLINGE-SCROLL 1/10"
COMPOSIZIONE	COMPOSITION	COMPOSITION	POLNUTZSCHICHT
100% POLIAMMIDE SD	100% POLYAMIDE SD	100% POLYAMIDE SD	100% POLYAMID SD
SOTTOFONDO	SECONDARY BACKING	DOSSIER	RÜCKENAUSRÜSTUNG
POLYFLEX	POLYFLEX	POLYFLEX	POLYFLEX
PUNTI AL M ²	STITCHES PER M ²	TOUFFES AU M ²	KNOTEN M ²
± 213300	± 213300	± 213300	± 213300
ALTEZZA PELO	PILE HEIGHT	HAUTEUR DU VELOURS	POLHÖHE
± 2.9 mm	± 2.9 mm	± 2.9 mm	± 2.9 mm
ALTEZZA TOTALE	TOTAL HEIGHT	HAUTEUR TOTALE	GESAMTHÖHE
± 6.2 mm	± 6.2 mm	± 6.2 mm	± 6.2 mm
PESO FIBRA	YARN WEIGHT	POIDS DU VELOURS	POLGEWICHT
± 650 g/m ²	± 650 g/m ²	± 650 g/m ²	± 650 g/m ²
PESO TOTALE	TOTAL WEIGHT	POIDS TOTAL	GESAMTGEWICHT
± 4200 g/m ²	± 4200 g/m ²	± 4200 g/m ²	± 4200 g/m ²
DIMENSIONI QUADROTTA	TILE SIZE	TAILLES DES DALLE	GESAMTGEWICHT
50x50 cm	50x50 cm	50x50 cm	50x50 cm
MADRID	MADRID	MADRID	MADRID



BUSINESS WEARABILITY: ★ ★ ★

Colour fastness to light	> 5	Thermal resistance m ² K/W	≤ 0,17
Insulation impact noise ΔLw	24 dB	Body voltage walking test kV	≤ 2