

OSLO

RADICI
CARPET



Specifications and tolerances in according EN 1307

Costruzione	Construction	Technique de fabrication	Herstellungsverfahren
TUFTING RICCIO- SCROLL 1/10"	TUFTED LOOP PILE -SCROLL 1/10"	TUFTED BOUCLÉ -SCROLL 1/10"	GETUFTED SCHLINGE-SCROLL 1/10"
Composizione	Composition	Composition	Polnutschicht
100% POLIAMMIDE SD	100% POLYAMIDE SD	100% POLYAMIDE SD	100% POLYAMID SD
Sottofondo	Secondary Backing	DOSSIER	RÜCKENAUSRÜSTUNG
POLYFLEX	POLYFLEX	POLYFLEX	POLYFLEX
Punti al M ²	Stitches per M ²	Touffes au M ²	Knoten M ²
± 208820	± 208820	± 208820	± 208820
Altezza pelo	Pile Height	Hauteur du velours	Polhöhe
± 2.5 mm	± 2.5 mm	± 2.5 mm	± 2.5 mm
Altezza totale	Total Height	Hauteur totale	Gesamthöhe
± 5.4 mm	± 5.4 mm	± 5.4 mm	± 5.4 mm
Peso fibra	Yarn Weight	Poids du velours	Polgewicht
± 550 g/m ²	± 550 g/m ²	± 550 g/m ²	± 550 g/m ²
Peso totale	Total Weight	Poids total	Gesamtgewicht
± 4000 g/m ²	± 4000 g/m ²	± 4000 g/m ²	± 4000 g/m ²
Dimensioni quadrata	Tile Size	Tailles des dalle	Gesamtgewicht
50x50 cm	50x50 cm	50x50 cm	50x50 cm
OSLO	OSLO	OSLO	OSLO



BUSINESS WEARABILITY: ★ ★ ★

Colour fastness to light	> 5	Thermal resistance m ² K/W	≤ 0,17
Insulation impact noise ΔLw	24 dB	Body voltage walking test kV	≤ 2