

	EN	DE	FR	NL	PL	HU	STANDARD	RESULT
	Size	Größe	Format	Afmeting	Wymiar	Méret	EN ISO 24342	See page 3
	Thickness	Gesamtdicke	Épaisseur	Dikte	Grubość catkowita	Vastagság	EN ISO 24346	6,5 mm
	Wear layer	Nutzschichtdicke	Couche d'usure	Slijtlaag	Grubość warstwy użytkowej	Kopóréteg	EN ISO 24340	0,55 mm
	Locking mechanism ¹	Verriegelungssystem ¹	Système d'emboîtement breveté ¹	Kliksysteem ¹	Mechanizm blokujący ¹	Zármechanizmus ¹		5G® fold down installation system ^{1 2}
	Surface treatment	Oberflächenbeschichtung	Traitement de surface	PU-coating	Zabezpieczenie powierzchni	Felületkezelés		K-Guard+® PU coating
	Warranty ³	Garantie ³	Garantie ³	Garantie ³	Gwarancja ³	Garancia ³	Commercial	15 years
							Residential	30 years
	Bevelled edge	Abgeschrägte Kante	Chanfrein	V-groef	Fazowanie	Leélezett szél		Micro
	Mass per unit area	Flächengewicht	Masse surfacique	Gewicht	Waga catkowita	Egységnyi területére jutó tömeg	EN ISO 23997	7480 g/m ²
	Standards	Belagsart	Type de revêtement	Soort vloerbekleding	Rodzaj wykładziny	Szabványok	EN 16511	Pass (multilayer modular floorcovering panels)
	Classification	Klassifizierung	Classification	Classificatie	Klaszifikacja użytkowa	Besorolás	ISO 10874 - Commercial	33: Commercial heavy
							ISO 10874 - Domestic	23: Domestic heavy
	Reaction to fire	Entflammbarkeit	Réaction au feu	Vuurbestendigheid	Klasa ogniotrwałości	Tűzzel szembeni viselkedés	EN 13501-1	Bfl-s1
	Staining resistance	Farbbeständigkeit	Résistance aux taches	Vlekbestendigheid	Odporność chemiczna	Foltállóság	EN 438-2	Pass (Grade 5)
	Light fastness	Lichtbeständigkeit	Solidité des couleurs à la lumière	Lichtvastheid	Odporność barwy na światło	Fényállóság	EN ISO 105-B02	Pass (≥ 6)
	Abrasion resistance	Abnutzungsbeständigkeit	Résistance à l'abrasion	Krasvastheid	Grupa ścieralności	Kopásállóság	EN 13329 Annex E	Pass (> 4000 cycles)
	Furniture chair leg	Möbelfuß	Pied d'ameublement	Meubelpoot	Nacisk punktowy mebli	Bútorláb	EN 424	Pass (No visible damage)
	Dimensional stability	Maßstabilität	Stabilité dimensionnelle	Dimensionale stabiliteit	Stabilność wymiarowa	Mérettartás	BS EN ISO 23999	Pass (≤ 0,25%)
	Swelling	Wölbung	Gonflement	Zwelling	Wybrzuszenie	Hullámosodás	ISO 24336	Pass (0,2%)
	Acoustic impact noise reduction	Schalldämmung	Bruit d'impact	Geluidsdemping	Absorpcja akustyczna	Akusztiqus hatás – zajcsökkentés	EN ISO 10140-1:2016 and EN ISO 10140-3:2010+A1:2015	ΔLw = 21 dB ALLIN = 11 dB

	EN	DE	FR	NL	PL	HU	STANDARD	RESULT
	Indentation - residual	Resteindruck	Poinçonnement rémanent	Indrukgevoeligheid	Wgniecenie resztkowe	Karcolódás – megmaradó	EN 433/EN ISO 24343-1	Pass (≤ 0,1 mm)
	Impact resistance	Schlagfestigkeit	Résistance à l'impact	Impactbestendigheid	Odporność na uderzenia	Ütésállóság	EN 13329 Annex F	Pass (≥ 1800 mm)
	Castor chair continuous use	Stuhlrollenbeanspruchung	Usure due aux chaises à roulettes	Bureaustoeltest bij continu gebruik	Oddziaływanie: krzesła na rolkach	Folyamatos görgősszék-használat	EN 425/ISO 4918	Pass (25 000 cycles)
	Thermal resistance	Wärmedurchlässigkeit (Widerstand)	Résistance thermique	Warmteweerstand	Przewodzenie ciepła	Hőállóság	ISO 8302	0,0515 m²K/W
							Underfloor heating	Suitable. Max 27°C
	Slip resistance ⁴	Rutschfestigkeit ⁴	Glissance ⁴	Slipweerstand ⁴	Właściwości antypoślizgowe ⁴	Csúszásgátló képesség ⁴	EN 13893	DS
							DIN 51130	R10
	Adhesive	Klebstoff	Colle	Lijm	Klej	Ragasztó		None; refer to installation instructions
	Environmental	Umwelt	Environnement	Milieu	Środowisko	Környezeti	Eurofins Indoor Air Comfort	Gold
							Floorscore SCS-EC10.3-2014 v4.0	Certified
							ISO 14001 / ISO 9001	Manufactured in certified facilities
	CE / DOP	CE / DOP	CE / DOP	CE / DOP	CE / DOP	CE / DOP	EN 14041	DOP 2022/6.5RC/EN/01
	Recycling	Recycling	Recyclable	Recyclebaar	Recykling	Újrafeldolgozhatóság		Suitable
	Phthalate free	Phthalatfrei	Sans phtalates	Ftalaatvrij	Nie zawiera ftalanów	Nem tartalmaz ftalátokat		Yes

¹ 5G® and 2G™ are patented technologies invented by Välinge Innovation AB. The 5G® and 2G™ word mark and logo are registered trademarks owned by Välinge Innovation AB and any use of such marks is under license.

² 5G® short edge; 2G™ long edge except SM-VGW121T-RKP, SM-VGW122T-RKP, SM-VGW126T-RKP which are modified 2G™ on short edge and standard 2G™ on long edge.

³ Subject to terms. Please see our website.

⁴ Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

Plank/Tile	Size (mm)	Size (in)	Box qty (m ²)	Box qty (pieces)	Slip resistance
Plank	1420,0 x 225,0	55,91 x 8,86	3,195	10	R10
Plank	708,0 x 177,0	27,87 x 6,97	3,008	24	R10
Tile	457,0 x 600,0	17,99 x 23,62	2,742	10	R10
Tile	457,0 x 935,0	17,99 x 36,81	2,564	6	R10