




















Product quality		
<b>Format</b>	488 x 118 x 2.5 mm	
<b>Packaging</b>	<b>Pack:</b>	30 elements / 1.728 m <sup>2</sup> / 7.59 kg
	<b>Palette:</b>	132 packs / 228.096 m <sup>2</sup> / 1,037.88 kg
Tolerances (requirement EN ISO 10582)		
<b>Weight per unit area</b>	4,300 g/m <sup>2</sup> ± 5%	
<b>Squareness of the elements (≤ 0.25 mm)</b>	≤ 0,10 mm/m	
<b>Determination of linearity (≤ 0.35 mm/m)</b>	≤ 0,20 mm/m	
<b>Dimensional stability after exposure to heat (≤ 0,15 %)</b>	≤ 0,15 %	
<b>Curling after exposure to heat (≤ 1mm)</b>	≤ 1mm	
Guarantee (According Parador guarantee conditions)		Notes
Domestic area	Commercial area	- only suitable for all-over adhesion - cleaning and maintenance see instructions - technical changes reserved
Lifetime	10 years	
  		

Classification		
		
Utility class 23 = domestic areas with intensive use	Utility class 33 = commercial areas with intensive use	
The design floor meets all requirements of the designated utility class.		
Requirements / properties	Test method	Rating
 Wear layer	EN ISO 24340	0,55 mm
 Surface Coating		PUR
 Reaction to fire	EN 13501-1	B <sub>n</sub> s1
 Slip resistance	EN 13893 EN 14041	μ ≥ 0,30 DS
 Staining resistance	ISO 26987	Index 0, Not affected
 Light fastness	EN ISO 105 – B02	Blue wool scale: Stage ≥ 6
 Resistance to roller castor chairs	ISO 4918	Type W, no visible changes
 <b>Thermal resistance</b> Suitable for installation over underfloor heating	EN 12664	0,012 m <sup>2</sup> *K/W
 Moving a furniture leg	EN 424	No visible changes
 Indentation-residual	EN ISO 24343-1	≤ 0,10 mm
 Water resistance	EN 317	waterproof
 Antimicrobial activity	ISO 22196	Antibacterial
 Slip resistance	EN 16165, Annex B on an inclined plane	Matt finished texture: R10
	EN 16165, Annex C pendulum test	PTV (dry / wet) ≥ 36 Low slip potential according to UK Slip potential group
 Disposal	EAK-Code-number	20 01 39

Changed:	QMB Parador	File:	PA_TDS_Designboden_Vinyl_Dryback-TT10_EN_20250101
Date:	01.01.2025	Latest update at:	<a href="http://www.parador.de/en/services/downloads/design-flooring">www.parador.de/en/services/downloads/design-flooring</a>
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.01.2025