

Product quality				
Type	Stair treads		Stair landing aluminium profile	Flush side panel (can be used on left and right)
	Pack 1 (for 4 treads)	Pack 2 (for 4 treads)		
Content – part 1	2 double steps	2 double steps	1 piece	1 piece
Length x Width x Thickness	1150 x 670 x 60 mm	1380 x 670 x 60 mm		11 x 60 x 500 mm
Content - part 2	2 double risers	2 double risers		
Length x Width x Thickness	1150 x 380 x 8 mm	1380 x 380 x 8 mm		
Weight	24.7 kg/ package	29.6 kg/ package	0.46 kg	0.3 kg

Functional / Surface quality			
Based on the top layer and tested on a floor covering in accordance with EN 16511			
		Test method	Rating
	Slip resistance	EN 13893 EN 14041	$\mu \geq 0.30$ DS
	Staining resistance	EN 438-2	Category 1 + 2: level 5 Category 3: level 4/5
	Light fastness	EN ISO 105 – B02	Blue wool scale: Stage ≥ 6
	Moving a furniture leg	EN ISO 16581	No visible damage (foot type 0)
	Residual indentation	EN ISO 24343-1	≤ 0.05 mm
	Formaldehyde emission (E1 = 0.1 ppm)	ISO 16000	≤ 0.05 ppm
	Abrasion	ISO 24338, method B	$> 7,000$ rev.
	Impact resistance	EN 13329 Annex F	$\geq 1,800$ mm
	Dimensional stability after exposure to temperature	EN ISO 23999	≤ 0.15 %
	Micro scratch resistance	EN 16094	"Method A MSR-A2 For mat surfaces (gloss ≤ 7): ≤ 1.5 unit change at 60°"
	Slip resistance	EN 16165, Annex B on an inclined plane	R10
		EN 16165, Annex C pendulum test	"PTV (dry (slider 96)) ≥ 36 Low slip potential according to UK Slip resistance group"
	Disposal	EAK-Code-number	17 09 04 + 17 04 02 (for aluminium-profile)

Changed:	QM	File:	PA_TDS_Treppenstufen_EN_20260101
Date:	01.01.2026	Latest version at:	https://parador.de/en/services/downloads
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.01.2026